

Meter size

O.D. (mm)	O.D. tolerance	Standard Length(mm)	Length Tolerance
4	+0.60 -0.00mm		
5	+0.60 -0.00mm		
6	+0.60 -0.00mm		
7	+0.60 -0.00mm		
8	+0.60 -0.00mm		
9	+0.60 -0.00mm		
10	+6.0 -0.0 %		
11	+6.0 -0.0 %		
12	+6.0 -0.0 %		
13	+6.0 -0.0 %		
14	+6.0 -0.0 %		
15	+6.0 -0.0 %		
16	+6.0 -0.0 %		
17	+6.0 -0.0 %		
18	+6.0 -0.0 %		
20	+6.0 -0.0 %	1000	
22	+6.0 -0.0 %	2000	
25	+6.0 -0.0 %		
30	+6.0 -0.0 %		
35	+6.0 -0.0 %		+2.0% -0.0%
40	+6.0 -0.0 %		
45	+6.0 -0.0 %		
50	+6.0 -0.0 %		
55	+6.0 -0.0 %		
60	+6.0 -0.0 %		
65	+6.0 -0.0 %		
70	+6.0 -0.0 %		
75	+6.0 -0.0 %		
80	+6.0 -0.0 %		
85	+6.0 -0.0 %		
90	+6.0 -0.0 %		
95	+6.0 -0.0 %		
100	+6.0 -0.0 %		
110	+6.0 -0.0 %		
120	+6.0 -0.0 %		
130	+6.0 -0.0 %	1000	
140	+6.0 -0.0 %		
150	+6.0 -0.0 %		
160	+6.0 -0.0 %		

Material: Virgin PTFE

Precision ground rods are available

Custom sizes